






Heyco® PG Thread Taps

For Steel Conduit Threads per DIN 40430



THREAD TYPE AND SIZE	TAP DRILL DIAMETER mm.	DESCRIPTION	PART NO.		PART DIMENSIONS		
			Starting	Finishing	Major Diameter mm.	Overall Length mm.	Thread mm.
PG 7	11,5	PG-T7	0150	0151	12,5	63,0	20,0
PG 9	14,0	PG-T9	0153	0154	15,2	70,0	20,0
PG 11	17,3	PG-T 11	0156	0157	18,6	80,0	22,0
PG 13.5	19,0	PG-T 13.5	0159	0160	20,4	80,0	22,0
PG 16	21,3	PG-T 16	0162	0163	22,5	80,0	22,0
PG 21	27,0	PG-T 21	0165	0166	28,3	90,0	22,0
PG 29	35,5	PG-T 29	0168	0169	37,0	110,0	25,0

- Use a starting tap for through-hole applications.
- For blind holes, thread first with a starting tap; finish bottoming the threads with a finishing tap.
- Flank angle 80°.
- Made of high-speed steel with ground threads for greater accuracy to assure optimum performance.
- Suitable for cutting alloy steel, bronze and stainless.



Heyco® Conduit & Fittings LabKit #69 (Part #3298)

ALL NEW LABKIT!

Use Heyco LabKits!

They are perfect for product design departments, experimental labs, and prototype work. Our kits contain an assortment of our most popular sizes of liquid tight cord grips.

Heyco also offers lab kits for our plugs, bushings, IEC connectors, wire connectors, and strain reliefs. Consult the appropriate catalog section.

PART NO.	COLOR	DESCRIPTION	APPROXIMATE QTY	CATALOG PAGE
8431	GRAY	HF1 1/2	2	0-15
8432	GRAY	HF1 3/4	2	0-15
8451	BLACK	HF2 1/2	2	0-16
8452	BLACK	HF2 3/4	2	0-16
8404	BLACK	HFC 3/4	1	0-19
8388	BLACK	HFC 3/4-S	1	0-18
8386	BLACK	HFC 1/2-S	1	0-18
9794	ZINC	HFC Z-1/2	2	0-24
8463	BLACK	NLN 1/2-NPT	10	0-26
8426	GRAY	HFC 1/2-90R	1	0-20
9796	ZINC	HFC Z-1/2-90	1	0-23
1027	BLACK	HFB 1/2	8	0-27
8495	BLACK	HFC 3/4-S-TWIST	2	0-21
8497	BLACK	HFC 3/4-NPT-TWIST	2	0-21
8490	BLACK	HFC 1/2-S-TWIST	4	0-21
8494	GRAY	HFC 1/2-NPT-TWIST	2	0-21
8513	GRAY	HFC 3/4-NPT-90-TWIST	1	0-22
8508	GRAY	HFC 1/2-NPT-90-TWIST	2	0-22
8505	BLACK	HFC 1/2-S-90-TWIST	2	0-22
8510	BLACK	HFC 3/4-S-90-TWIST	1	0-22