



Heyco® Back-Up Washers For Strain Relief Bushings



PART NO.	DESCRIPTION	INSIDE DIAMETER		OUTSIDE DIAMETER		THICKNESS	
		in.	mm.	in.	mm.	in.	mm.
7591	SRW 437	.437	11,1	.562	14,3	.025	0,6
7592	SRW 500	.500	12,7	.625	15,9	.025	0,6
7593	SRW 625	.625	15,9	.812	20,6	.025	0,6

- Made of zinc-plated steel.
- Used together with our Strain Relief Bushings.
- For situations where the panel is too flexible to support UL's 35# strain relief pull-out test.
- OR for situations where the panel is thin relative to the strain relief's locking slot. The backup washer eliminates "play".
- OR can be used to contain the strain relief bushing in U-slot openings.
- Quick Specs below don't apply.

Heyco® T-Bar



- **Part No. 3791**, T-bar available in **black only**.
- During cable removal or replacement, the T-Bar prevents complete removal of the strain relief bushing from the panel, reducing the risk of losing the bushing.
- Not for use in any mounting hole greater than .625" (16,0 mm) in diameter.
- Snap T-Bar onto the strain relief bushing strap (linking body to key piece), then feed it into the chassis mounting hole.

Material 6/6 "Nylon"
 Flammability Rating 94V-2
 Material Temperature Index 125°C—Maximum temperature on part not to exceed 105°C

*Quick
Specs*