


Heyco® Nytye® Mounting Platforms

- 6/6 "Nylon" with a 94V-2 flammability rating; temperature index 85°C.
- Eight sizes anchor Nytyes securely.
- Three styles:
 - 1) Adhesive-backed (may also be screw mounted, except MP-4A's)
 - 2) Screw mount
 - 3) Push mount
- Rubber based adhesive good up to 52°C.
- Recognized under the Component Program of Underwriters' Laboratories File #E-54523.

NYTYE INSERTION POINTS	MOUNTING STYLE	PART NO.	DESCRIPTION	SCREW SIZE		PART DIMENSIONS		USE WITH NYTYES OF MAX. TENSILE	
				No.	mm.	in.	mm.	Lb.	N.
		Natural							
4	Adhesive	3594	MP-4A-S			.800	20,3	40	178
2	Adhesive	3590	MP-2A	8	4,1	1.10	27,9	50	222
4	Adhesive	3593	MP-4A	6	3,5	1.15	29,2	50	222
2	Push Mount	3762	MP-PM-250	Mounts into .250" (6,4mm) Diameter hole.		.313 x .563	7,9 x 14,3	50	222
2	Screw	3759	MP-S-68	8	4,1	.375 x .625	9,5 x 15,9	50	222
2	Screw	3753	MP-S-10	10	5,1	.625 x .875	15,9 x 22,2	120	534
2	Screw	3756	MP LPM-56	5-6	—	.400 x .320	10,2 x 7,9	18	80
2	Screw	3757	MP LPM-68	6-8	—	.750 x .500	19,1 x 12,7	50	222


Standard Color: Natural.




MP-4A-S



MP-4A



MP-2A



MP-S-68
MP-S-10



MP-PM-250



MP-LPM



Heyco® Cable Tie Tensioning Tool

- **Part No. 0998** fits all standard duty Nytyes. Metal construction, has three tension settings, and automatically trims excess.

