



# Heyco® Braided Sleeving

BUNDLE RANGE				PART NO.	DESCRIPTION	PART DIMENSIONS			
Minimum Diameter		Maximum Diameter				Black	Nominal Diameter		Quantity Per Spool
in.	mm.	in.	mm.					ft.	mtrs.
.090	2,3	.250	6,4	<b>8980</b>	BS 125	.125	3,2	1,000	305
				<b>8983</b>	BS 125 FR				
.125	3,2	.437	11,1	<b>8985</b>	BS 250	.250	6,4	1,000	305
				<b>8988</b>	BS 250 FR				
.250	6,4	.750	19,1	<b>8990</b>	BS 500	.500	12,7	500	152
				<b>8993</b>	BS 500 FR				
.500	12,7	1.250	31,8	<b>8995</b>	BS 750	.750	19,1	250	76
				<b>8998</b>	BS 750 FR				
.750	19,1	1.750	44,5	<b>9000</b>	BS 1250	1.250	31,8	250	76
				<b>9003</b>	BS 1250 FR				
1.250	31,8	2.750	69,9	<b>9005</b>	BS 1750	1.750	44,5	200	61
				<b>9008</b>	BS 1750 FR				
1.500	38,1	3.500	88,9	<b>9010</b>	BS 2.0	2.000	50,8	200	61
				<b>9013</b>	BS 2.0 FR				
1.750	44,5	4.500	114,3	<b>9015</b>	BS 2.5	2.500	63,5	200	61
				<b>9018</b>	BS 2.5 FR				

Standard Color: Black.  
FR sleeving flammability rating—UL VW-1.



- Tough, cut-resistant over sleeving is designed for protecting wire bundles and harnesses, hoses, tubing, and cable assemblies from mechanical damage and environmental hazards.
- Preferred cutting method: hot knife.
- Expandable up to three times its own diameter, the open-weave construction can fit many applications, simplifying inventory. The open-weave allows for easy inspection of sleeved components and easy break out of individual cables.
- Full cable flexibility is maintained in any direction, even at low temperatures. Wires encased in Heyco Braided Sleeving can FLEX and bend as readily as if they had no protective oversleeving. Bundles can be flexed repeatedly without damage.
- Braided sleeve slips on quickly and is self-fitting over irregular shapes and contours. No wire pulling compounds are required due to its low surface friction. Slight tensioning after application makes for an even tighter fit.
- The high tensile strength, damage-resistant filament braid:
  - 1) protects against rough surfaces, sharp edges or corners
  - 2) resists scuffing and abrasion
  - 3) cushions against vibration and impact damage
  - 4) prevents condensation while allowing complete drainage
  - 5) dissipates heat and moisture
  - 6) does not degrade in most fluid environments
- Sleeved components are more organized and attractive!

**Material Certifications**

Polyester Monofilament Yarns or Flame Retardant Polyester Yarn  
 Recognized under the Component Program of Underwriters' Laboratories File #E-173954

Monofilament Diameter .010"  
 Continuous Operating Temperature -75°C to 125°C

*Quick Specs*