

	COLOR	VISCOSITY	TEMP RANGE	HARDNESS	TAC FREE	PACKAGING
<i>FLEX SILICONE SERIES – One Part Silicones</i>						
<i>FLEX 1100</i> Multi-purpose silicone for use in numerous bonding and sealing applications. (Acetoxy)	Clear, Black, Blue, White, Aluminum	Non-Sag Gel	-85 to 450° F	30 Shore A	15-20 Min.	10.3 oz. cart 4.5 gal pail 55 gal. drum
<i>FLEX 1200</i> Low odor silicone, neutral cure sealant, fast curing, used in many of the same applications as FLEX 1100. (Oxime)	Clear, White	Non-Sag Gel	-85 to 450° F	28 Shore A	15-20 Min.	10.3 oz. cart 4.5 gal pail 55 gal. drum
<i>FLEX 1300</i> High performance, high temperature adhesive/sealant. Continuous temperature resistance to 500° F, intermittent to 600° F. (Acetoxy)	Red	Non-Sag Gel	-85 to 500° F	30 Shore A	15-20 Min.	10.3 oz. cart 4.5 gal pail 55 gal. drum

Packaging: Flex Silicone products are available in 3 ounce tubes, 10.3 ounce cartridges, 5 gallon pails, and 55 gallon drums. Special packaging is available upon request.